

## DSP80T

### 100W Ultra-Thin Wall Mount Speaker



#### Description

The DSP80T ultra-thin wall mount speaker offers a modern, stylish, and aesthetically pleasing appearance, while achieving excellent sound quality. Blending modern home design concepts, the ultra-thin cabinet is designed for wall mounting, transforming it into a natural artistic decoration that seamlessly integrates with its surroundings. The ultra-thin wall mount speaker features the exclusive "Super Speaker Unit," allowing for a wider frequency response and lower frequency range within its thin body. The sound is clear, with good transient response, low distortion, excellent directivity, and a long transmission distance. The cabinet is lightweight, with a sleek and flexible design, truly merging sound and art. It is the best choice for high-end conference venues, hotels, and business reception centers.

The DSP80T ultra-thin wall mount speaker system uses an exclusive super speaker unit. The entire cabinet is designed with an aluminum profile molding structure. From an acoustic perspective, this design eliminates the conditions for internal standing waves and offers excellent rigidity, resulting in extremely low sound coloration. It minimizes any adverse effects on sound reproduction, providing clear and natural speech as well as exhilarating music. The ultra-thin full-range speaker can effortlessly deliver these qualities.

The DSP80T ultra-thin wall mount speaker comes with a Clip-on Wall Mount Bracket for easy installation on site. The sound output is designed with a professional 2-position terminal block, making it suitable for various installation environments.

This system is ideal for small mobile performances, stadiums, theaters, bars, banquet halls, and other similar venues.

## Features

- Full range, bass-reflex passive speaker system.
- Equipped with 4 Super Speakers and 1 Tweeter.
- Rated power 100W @8Ω, peak power 40W
- Sensitivity 91±2dB.
- Cover range: H 120° × V 120 °.
- Its cabinet boasts an aluminum panel and wooden frame with a sandblasted finish for a high-end look.
- Includes a professional 2-position terminal block for speaker connections.
- Offers wide frequency range and deep bass, ideal for speeches and music.
- Suited for small to medium venues and conference rooms with high standards.

## Specifications

Model	DSP80T
Frequency Response	125Hz-20kHz
Sensitivity	91dB±2dB
Coverage Angle(Horizontal x Vertical )	H120°× V120°
Power Parameter	100W Continuous, 400W Peak
Driver Unit	4x20W Super Speakers +1x Treble
Nominal Impedance	8 Ohms
Wiring Terminal	1x2-Position Terminal Block
Speaker Enclosure Material	Aluminum Panel+MDF Wooden Frame
Speaker Dimension (H×W×D)	950mm×135mm×26mm
Net Weight	4.2kg (Including Bracket)

## Product Information

